


CNC 走乢自動車床刀具 TURNING TOOLS FOR AUTOMATIC LATHES










Right-hand shown

Item code	Dimensions,mm					Insert	Screw	Wrench	Weight
	H (H1)	В	L	L1	Т	moort		0	Kg
SDKGR/L-1010K-353	10	10	125	11	3	DK3	MS4009A	ETF15	0.10
SDKGR/L-1212M-353	12	12	150	11	3				0.17
SDKGR/L-1616M-353	16	16	150	11	3				0.30
SDKGR/L-2020K-353	20	20	125	11	3				0.42
SDKGR/L-2525M-353	25	25	150	11	3				0.74
SDKGR/L-1010K-354	10	10	125	11	4	DK4	MS4009A	ETF15	0.10
SDKGR/L-1212M-354	12	12	150	11	4		MS4011A		0.17
SDKGR/L-1616M-354	16	16	150	11	4				0.30
SDKGR/L-2020K-354	20	20	125	11	4				0.42
SDKGR/L-2525M-354	25	25	150	11	4				0.74




被切削材 Workpiece material	Steel 鋼	Р	•	•	
	Stainless steel 不銹鋼	М	•	•	
	Cast iron 鑄鐵	K	•	•	
	Non-ferrous metal 非鐵金屬	Ν			•

			GRADE 材質			Dimonoiono mm					
Insert Sha	pe	Description	Coate	d 塗層	Uncoated 無塗層	Dimensions,mm					
			GT29	GA49	GX06	S	W	Re	L2	K°	Pitch (mm)
	斷屑槽 breaker	DKTR-4305510	•	0	•	4	3.0	0.1	6	55	0.1-3
		DKTR-4206005	•	0	•	4	2.0	0.05	6	60	0.05-2
		DKTR-4306010	•	0	•	4	3.0	0.1	6	60	0.1-3
		DKTL-4206005	•	0	•	4	2.0	0.05	6	60	0.05-2
R L		DKTL-4306010	•	0	•	4	3.0	0.1	6	60	0.1-3
牙刀片 Threading		DKTL-4306020				4	3.0	0.2	6	60	0.2-3
		DKRR-4050R25	•	0	•	4	1.0	0.50	2.5		
		DKRR-4075R50	•	0	•		1.5	0.75	5.0		
		DKRR-4100R60	•	0			2.0	1.00	6.0		
	斷屑槽	DKRR-4125R80		0			2.5	1.25	8.0		
	breaker W Re	DKRR-4150R80		0			3.0	1.50	8.0		
R L 圓槽刀片 Insert with radius		DKRR-4175RA0		0	•		3.5	1.75	10.0		
		DKRR-4200RA0	•	0			4.0	2.00	10.0		
		DKRL-4050R25	•	0		4	1.0	0.50	2.5		
		DKRL-4075R50		0	•		1.5	0.75	5.0		
		DKRL-4100R60	•	0	•		2.0	1.00	6.0		
		DKRL-4125R80	•	0	•		2.5	1.25	8.0		
		DKRL-4150R80	•	0	•		3.0	1.50	8.0		
		DKRL-4175RA0	•	0	•		3.5	1.75	10.0		
		DKRL-4200RA0		0	•		4.0	2.00	10.0		
	斷屑槽 breaker Re_ W _Re	DKGR-4100-1025	•	•	•	4	1.0	0.1	2.5		
		DKGR-4150-1030	•	•	•		1.5	0.1	3.0		
		DKGR-4200-1040	•		•		2.0	0.1	4.0		
		DKGR-4250-1060	•		•	4	2.5	0.1	6.0		
		DKGR-4300-1080					3.0	0.1	8.0		
	27	DKGL-4100-1025	•	0	•		1.0	0.1	2.5		
		DKGL-4150-1030	•	0	•		1.5	0.1	3.0		
R L		DKGL-4200-1040					2.0	0.1	4.0		
插掃刀片 Grooving and turning		DKGL-4250-1060	•	0			2.5	0.1	6.0		
Grooving and turning		DKGL-4300-1080		0			3.0	0.1	8.0		
R		DKGR-4100-1025P	•	0		4	1.0	0.1	2.5		
	Re W Re	DKGR-4150-1030P	•	0			1.5	0.1	3.0		
		DKGR-4200-1040P	•	0			2.0	0.1	4.0		
		DKGR-4250-1060P	•	0			2.5	0.1	6.0		
	77	DKGR-4300-1080P	•		•		3.0	0.1	8.0		
插掃刀片 Grooving and turning	無斷屑槽 No breaker										

CNC 走心目動車床刀具 TURNING TOOLS FOR AUTOMATIC LATHES





	Steel 鋼	Р	•	•	
被切削材	Stainless steel 不銹鋼	М	•	•	
Workpiece material	Cast iron 鑄鐵	K	•	•	
	Non-ferrous metal 非鐵金屬	Ν			

				RADE		Dimensions,mm					
Insert Sha	ре	Description	Coate	d 塗層	Uncoated 無塗層			,			
			GT29	GA49	GX06	S	W	Re	L2	K°	
		DKBR-33005	•	0	•	3	3.0	0.05	8.5	35	
		DKBR-33010		0	•		0.0	0.1	0.0		
		DKBR-33020		O				0.2			
		DKBR-43005		0	•	4	3.0	0.05	8.5	35	
		DKBR-43010		0	•			0.1			
		DKBR-43020	•	0	•			0.2			
		DKBR-44005		0	•	4	4.0	0.05	8.5	35	
	W_Re	DKBR-44010		0				0.1			
1 1	3	DKBR-44020	•	0	•			0.2			
		DKBL-33005	•	0	•	3	3.0	0.05	8.5	35	
	κ•	DKBL-33010	•	0				0.1			
R L		DKBL-33020		0				0.2			
後掃刀片 Back turning		DKBL-43005	•	0		4	3.0	0.05	8.5	35	
		DKBL-43010	•	0				0.1			
		DKBL-43020	•	0	•			0.2			
		DKBL-44005		0		4	4.0	0.05	8.5	35	
		DKBL-44010	•	0	•			0.1			
		DKBL-44020		0				0.2			
	斷屑槽 breaker	DKCR-3150R-1085		•	•	3	1.5	0.1	8.5	15	
		DKCR-3200R-10A5					2.0		10.5		
		DKCR-3250R-10A5		•			2.5				
		DKCR-3300R-10A5		•	•		3.0				
		DKCL-3150L-1085	•	0	•	3	1.5	0.1	8.5 10.5	15	
		DKCL-3200L-10A5	•	0	•		2.0				
		DKCL-3250L-10A5	•	0	•		2.5				
R L 切斷刀片 Parting off		DKCL-3300L-10A5	•	0			3.0				
		DKPR-3150R-1085	•	0	•	3	1.5	0.1	8.5	15	
		DKPR-3200R-10A5	•	0	•		2.0		10.5		
		DKPR-3250R-10A5		0	•		2.5				
	無斷屑槽	DKPR-3300R-10A5		0			3.0	0 :		4-	
R L 切斷刀片 Parting off	No breaker W _Re	DKPL-3150L-1085		0	•	3	1.5	0.1	8.5	15	
		DKPL-3200L-10A5		0			2.0		10.5		
		DKPL-3250L-10A5 DKPL-3300L-10A5		0			2.5 3.0				
	75 75	DVLT-2200F-10W2					3.0				