



Coolant steel shank (right shown)
中心出水鋼柄 右向示意圖

Steel shank Item code		Dimensions,mm							Insert	Spare parts	Weight Kg	
無水孔Non-coolant	水孔Coolant	D	L	L1	F	H	K	dmin				
S16Q-SVUBR/L-11	A16Q-SVUBR/L-11	16	180	30	13	15	7	22	VB..1103..	①	0.28	
S20R-SVUBR/L-11	A20R-SVUBR/L-11	20	200	40	15	18	7	27			0.49	
S25R-SVUBR/L-16	A25R-SVUBR/L-16	25	200	45	18	23	5	32		VB..1604..	②	0.77
S25S-SVUBR/L-16	A25S-SVUBR/L-16	25	250	45	18	23	5	32				0.96
S32S-SVUBR/L-16	A32S-SVUBR/L-16	32	250	50	22	30	5	40			③	1.58
S40T-SVUBR/L-16	A40T-SVUBR/L-16	40	300	55	27	37	5	50				2.96
S40U-SVUBR/L-16		40	350	55	27	37	5	50				3.45
S40V-SVUBR/L-16		40	400	55	27	37	5	50				3.95
S12M-SVUCR/L-08	A12M-SVUCR/L-08	12	150	26	9.5	11	10	16	VC..0802..	④	0.13	
S1612M-SVUCR/L-08	A1612M-SVUCR/L-08	16	150	31	9.5	15	10	16			0.24	
S16Q-SVUCR/L-11	A16Q-SVUCR/L-11	16	180	30	13	15	7	22	VC..1103..	①	0.28	
S20R-SVUCR/L-11	A20R-SVUCR/L-11	20	200	40	15	18	7	27			0.49	
S25R-SVUCR/L-16	A25R-SVUCR/L-16	25	200	45	18	23	5	32	VC..1604..	②	0.77	
S25S-SVUCR/L-16	A25S-SVUCR/L-16	25	250	45	18	23	5	32			0.96	
S32S-SVUCR/L-16	A32S-SVUCR/L-16	32	250	50	22	30	5	40	VC..1604..	③	1.58	
S40T-SVUCR/L-16	A40T-SVUCR/L-16	40	300	55	27	37	5	50			2.96	
S40U-SVUCR/L-16	A40U-SVUCR/L-16	40	350	55	27	37	5	50			3.45	
S40V-SVUCR/L-16	A40V-SVUCR/L-16	40	400	55	27	37	5	50			3.95	

Insert	Spare parts	Shim	Screw	Wrench	Screw	Wrench
VB/VC..1103..	①	--	--	--	MS2506A	ETF09
VB/VC..1604..	②	--	--	--	MS3509B	ETF15
VB/VC..1604..	③	VSS322	MDS05035S	PL35	MS3512B	ETF15
VC..0802..	④	--	--	--	MS2005A	ETF06

內徑車刀
BORING BARS

外徑車刀
TOOL HOLDERS

牙刀 & 開槽刀
THREADING & GROOVING

銑刀
MILLING

孔加工
BORING TOOLS COMPONENTS

配件
SPARE PARTS